RETAIL ENVIRONMENTS

ASSEMBLY GUIDE CLASSIC VINYL BANNER GUIDE

BANNER GROMMETS & WIND SLITS

Banner installations should utilize all available grommets to safely secure it to where it's going to be used. We place grommets an average of every 2 feet, depending on banner size, free of charge.

We highly recommend getting wind slits cut into your banner if it's large and going to be placed outside. Banners without wind slits can act as a sail when placed outside and can be destroyed in the wind and elements.

BANNER HANGING METHODS

- Hang with rope: thread nylon rope through the grommets and attach to supports on each corner.
- Hang with Bungee Cords: hook one end into the corner grommet and then around your support structure. You will need to do this on all 4 corners.
- Hang with Zip Ties: zip ties make it very easy to install on a fence or a similar structure.
- Hang on a building or wall: place a washer over the grommet and use a screw to secure the banner. Sewn-in webbing: with additional webbing for tying to supports.



HELPFUL TIPS!

- The outdoor elements will damage your banner over time. Store your banner out of the sun, in a completely dry place, away from moisture when not in use.
- Roll up the banner with the print side inside. Do not fold the banner ink to ink side, this will cause a print transfer, scratches and destroy your banner.
- You can clean your banner with a damp cloth, mild soap and water. Make sure you rinse completely.
- Using harsh cleaners or solvents will destroy the print. When your banner has ripped or torn, it's time to replace your item.

